

PRODUCT CONTROL NOTICE OF ACCEPTANCE

Yale Ogron Manufacturing Co., Inc. 671 West 18 Street Hialeah,FL 33010

BUILDING CODE COMPLIANCE OFFICE

METRO-DADE FLAGLER BUILDING 140 WEST FLAGLER STREET, SUITE 1603 MIAMI, FLORIDA 33130-1563 (305) 375-2901 FAX (305) 375-2908

CONTRACTOR LICENSING SECTION

(305) 375-2527 FAX (305) 375-2558

CONTRACTOR ENFORCEMENT DIVISION (305) 375-2966 FAX (305) 375-2908

> PRODUCT CONTROL DIVISION (305) 375-2902 FAX (305) 372-6339

Your application for Notice of Acceptance (NOA) of:

Exterior Glazed Aluminum Fixed Window - Non-Impact & Large Missile Impact Resistant under Chapter 8 of the Code of Miami-Dade County governing the use of Alternate Materials and Types of Construction, and completely described herein, has been recommended for acceptance by the Miami-Dade County Building Code Compliance Office (BCCO) under the conditions specified herein.

This NOA shall not be valid after the expiration date stated below. BCCO reserves the right to secure this product or material at any time from a jobsite or manufacturer's plant for quality control testing. If this product or material fails to perform in the approved manner, BCCO may revoke, modify, or suspend the use of such product or material immediately. BCCO reserves the right to revoke this approval, if it is determined by BCCO that this product or material fails to meet the requirements of the South Florida Building Code.

The expense of such testing will be incurred by the manufacturer.

ACCEPTANCE NO.: 01-0102.05 EXPIRES: 12/13/2006

Raul Rodriguez

Chief Product Control Division

THIS IS THE COVERSHEET, SEE ADDITIONAL PAGES FOR SPECIFIC AND GENERAL CONDITIONS BUILDING CODE & PRODUCT REVIEW COMMITTEE

This application for Product Approval has been reviewed by the BCCO and approved by the Building Code and Product Review Committee to be used in Miami-Dade County, Florida under the conditions set forth above.

Francisco J. Quintana, R.A.

Francises / accintera

Director

Miami-Dade County

Building Code Compliance Office

APPROVED: 12/13/2001

Yale Ogron Mfg. Co.

ACCEPTANCE No.: 01-0102.05

APPROVED

. DEC 1 3 2001

EXPIRES

DEC 1 3 2006

NOTICE OF ACCEPTANCE: SPECIFIC CONDITIONS

1. **SCOPE**

1.1 This approves an aluminum fixed window system, as described in Section 2 of this Notice of Acceptance, designed to comply with the South Florida Building Code, 1994 Edition for Miami-Dade County, for the locations where the pressure requirements, as determined by SFBC Chapter 23, do not exceed the Design Pressure Rating values indicated in the approved drawings.

PRODUCT DESCRIPTION 2.

2.1 The Exterior Glazed Aluminum Fixed Window - Non-Impact & Large Missile Impact Resistant and its components shall be constructed in strict compliance with the following documents: Drawing No. W00-53, Sheets 1 through 6 of 6, titled "Exterior Glazed Alum Fixed Window", prepared by Al Farooq Corporation, dated 12/12/00 and revised on 10/2/01, signed and sealed by Humayoun Farooq, P.E., bearing the Miami-Dade County Product Control Approval stamp with the Notice of Acceptance number and approval date by the Miami-Dade County Product Control Division. These documents shall hereinafter be referred to as the approved drawings.

3. LIMITATIONS

- 3.1 This approval applies to single unit applications only, as shown in approved drawings.
- 3.2 For Design Pressure Rating vs. Window Size, see Comparative Analysis Tables in approved drawings.

4. **INSTALLATION**

- The aluminum fixed window system and its components shall be installed in strict compliance with 4.1 the approved drawings.
- Hurricane protection system (shutters): to determine whether the installation requires a hurricane protection system or not, see corresponding table in approved drawing.

5. **LABELING**

5.1 Each panel shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved".

6. **BUILDING PERMIT REQUIREMENTS**

- **6.1** Application for building permit shall be accompanied by copies of the following:
 - This Notice of Acceptance.
 - 6.1.2 Duplicate copies of the approved drawings, as identified in Section 2 of this Notice of Acceptance, clearly marked to show the components selected for the proposed installation.
 - 6.1.3 Any other documents required by the Building Official or the South Florida Building Code (SFBC) in order to properly evaluate the installation of this system.

Manuel Perez, P.E. Product Control Examiner

Product Control Division

Yale Ogron Mfg. Co.

ACCEPTANCE No).:	01-0102.05	
APPROVED	:	DEC 1 3 2001	
EXPIRES	:	DEC 1 3 2006	

NOTICE OF ACCEPTANCE: STANDARD CONDITIONS

- Renewal of this Acceptance (approval) shall be considered after a renewal application has been filed and the original submitted documents, including test-supporting data, engineering documents, are no older than eight (8) years.
- 2. Any and all approved products shall be permanently labeled with the manufacturer's name, city, state, and the following statement: "Miami-Dade County Product Control Approval", or as specifically stated in the specific conditions of this Acceptance.
- 3. Renewals of Acceptance will not be considered if:
 - a. There has been a change in the South Florida Building Code affecting the evaluation of this product and the product is not in compliance with the code changes.
 - b. The product is no longer the same product (identical) as the one originally approved.
 - c. If the Acceptance holder has not complied with all the requirements of this acceptance, including the correct installation of the product.
 - d. The engineer who originally prepared, signed and sealed the required documentation initially submitted, is no longer practicing the engineering profession.
- 4. Any revision or change in the materials, use, and/or manufacture of the product or process shall automatically be cause for termination of this Acceptance, unless prior written approval has been requested (through the filing of a revision application with appropriate fee) and granted by this office.
- 5. Any of the following shall also be grounds for removal of this Acceptance:
 - a. Unsatisfactory performance of this product or process.
 - b. Misuse of this Acceptance as an endorsement of any product, for sales, advertising or any other purposes.
- 6. The Notice of Acceptance number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the Notice of Acceptance is displayed, then it shall be done in its entirety.
- 7. A copy of this Acceptance as well as approved drawings and other documents, where it applies, shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at all time. The engineer need not reseal the copies.
- 8. Failure to comply with any section of this Acceptance shall be cause for termination and removal of Acceptance.
- 9. This Notice of Acceptance consists of pages 1, 2 and this last page 3. **END OF THIS ACCEPTANCE**

Manuel Perez, P.E., Product Control Examiner
Product Control Division

Yale Ogron Mfg. Co.

ACCEPTANCE No.: 01-0102.05

APPROVED

: DEC 1 3 2001

EXPIRES

DEC 1 3 2006

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

(For File ONLY. Not part of NOA.)

A. DRAWINGS

1. Manufacturer's die drawings and sections.

2. Drawing No. WOO-53, Sheets 1 through 6 of 6, titled "Exterior Glazed Alum Fixed Window", prepared by Al Farooq Corporation, dated 12/12/00 and revised on 10/2/01, signed and sealed by Dr. Humayoun Farooq, P.E.

B. TESTS

1. Test report on: 1) Air Infiltration Test, per PA 202-94

- 2) Uniform Static Air Pressure Test, Loading per PA 202-94
- 3) Water Resistance Test, per PA 202-94

along with installation diagram of an aluminum fixed arch window (3/16" temp), prepared by Hurricane Engineering & Testing Inc., Report No. **HETI-00-1174A**, dated 10/19/00, signed and sealed by Arshad Viqar, P.E.

- 2. Test report on: 1) Air Infiltration Test, per PA 202-94
 - 2) Uniform Static Air Pressure Test, Loading per PA 202-94
 - 3) Water Resistance Test, per PA 202-94

along with installation diagram of an aluminum fixed rectangular window (3/16" ann), prepared by Hurricane Engineering & Testing Inc., Report No. **HETI-00-1174B**, dated 10/19/00, signed and sealed by Arshad Viqar, P.E.

- 3. Test report on: 1) Air Infiltration Test, per PA 202-94
 - 2) Uniform Static Air Pressure Test, Loading per PA 202-94
 - 3) Water Resistance Test, per PA 202-94

along with installation diagram of an aluminum fixed rectangular window (3/16" temp), repared by Hurricane Engineering & Testing Inc., Report No. **HETI-001174C**, dated 10/19/00, signed and sealed by Arshad Viqar, P.E.

- 4. Test report on: 1) Air Infiltration Test, per PA 202-94
 - 2) Uniform Static Air Pressure Test, Loading per PA 202-94
 - 3) Water Resistance Test, per PA 202-94

along with installation diagram of an aluminum fixed rectangular window (3/16" temp), prepared by Hurricane Engineering & Testing Inc., Report No. **HETI-001174D**, dated 10/19/00, signed and sealed by Arshad Viqar, P.E.

- 5. Test report on: 1) Large Missile Impact Test per SFBC, PA 201-94
 - 2) Cyclic Wind Pressure Loading per SFBC, PA 203-94

along with installation diagram of an aluminum rectangular window (lam 3/16" HS), window, prepared by Hurricane Engineering & Testing Inc., Report No. **HETI-00-907A**, dated 12/6/00, signed and sealed by Arshad Vigar, P.E.

Manuel Perez, P.E. Product Control Examiner

Product Control Division

ACCEPTANCE No.: 01-0102.05

APPROVED

. DEC 1 3 2001

EXPIRES

DEC 1 3 2006

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

(For File ONLY. Not part of NOA.)

6. Test report on: 1) Air Infiltration Test, per PA 202-94

2) Uniform Static Air Pressure Test, Loading per PA 202-94

3) Water Resistance Test, per PA 202-94

along with installation diagram of an aluminum fixed rectangular window (lam 3/16" HS), prepared by Hurricane Engineering & Testing Inc., Report No. **HETI-00-1162**, dated 12/6/00, signed and sealed by Arshad Viqar, P.E.

- 7. Test report on: 1) Large Missile Impact Test per SFBC, PA 201-94
 2) Cyclic Wind Pressure Loading per SFBC, PA 203-94
 along with installation diagram of an aluminum fixed rectangular window (lam 3/16" HS), prepared by Hurricane Engineering & Testing Inc., Report No. **HETI-00-907B**, dated 12/6/00, signed and sealed by Arshad Viqar, P.E.
- 8. Test report on: 1) Large Missile Impact Test per SFBC, PA 201-94
 2) Cyclic Wind Pressure Loading per SFBC, PA 203-94
 along with installation diagram of an aluminum fixed arch window (lam 3/16" HS), prepared by Hurricane Engineering & Testing Inc., Report No. **HETI-00-916**, dated 12/6/00, signed and sealed by Arshad Viqar, P.E.
- 9. Test report on: 1) Air Infiltration Test, per PA 202-94
 - 2) Uniform Static Air Pressure Test, Loading per PA 202-94
 - 3) Water Resistance Test, per PA 202-94

along with installation diagram of an aluminum fixed rectangular window (3/16" ann),, prepared by Hurricane Engineering & Testing Inc., Report No. **HETI-00-1163**, dated 12/6/00, signed and sealed by Arshad Viqar, P.E.

- 10. Test report on: 1) Large Missile Impact Test per SFBC, PA 201-94
 2) Cyclic Wind Pressure Loading per SFBC, PA 203-94
 along with installation diagram of an aluminum fixed arch window (lam 3/16" HS), prepared by Hurricane Engineering & Testing Inc., Report No. HETI-00-917, dated 12/6/00, signed and sealed by Arshad Viqar, P.E.
- 11. Test report on: 1) Uniform Static Air Pressure Test, Loading per PA 202-94 along with installation diagram of an aluminum fixed rectangular window (1/8" ann), prepared by Hurricane Engineering & Testing Inc., Report No. **HETI-00-915**, dated 12/6/00, signed and sealed by Arshad Viqar, P.E.

C. CALCULATIONS

1. Anchor Calculations and structural analysis, prepared by Al Farooq Corporation, dated 12/11/00 and revised on 10/2/01, signed and sealed by Dr. Humayoun Farooq, P.E.

Manuel Perez, P.E. Product Control Examiner

Product Control Division

Ya	<u>le O</u>	gron	Mfg.	Co.

ACCEPTANCE No.: 01-0102.05

APPROVED

:DEC 1 3 2001

EXPIRES

. DEC 1 3 2006

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

(For File ONLY. Not part of NOA.)

D. MATERIAL CERTIFICATIONS


1. Notice of Acceptance No. **00-0524.06** issued to Nebula Glass International Inc. for "Glasslam Safety Plus," dated 9/21/00, expiring on 9/9/03.

2. Notice of Acceptance No. **98-0728.05** issued to Solutia Inc. for "Saflex IIIG PVB Polyvinyl butryal interlayer," dated 8/27/98, expiring on 5/21/01.

E. STATEMENTS

- 1. Letter by Al-Farooq Corporation, stating that the submitted drawings comply with the applicable sections of the South Florida Building Code, dated 2/6/01, signed and sealed by Dr. Humayoun Farooq, P.E..
- 2. Letter by Al-Farooq Corporation, stating that they have no financial interest with the laboratory that performed the tests or the engineer who witnessed the tests, dated 2/6/01, signed and sealed by Dr. Humayoun Farooq, P.E..
- 3. Letter by Yale Ogron Mfg. Co, stating that they have no financial interest with the laboratory that performed the tests or the engineer who witnessed the tests, dated 2/5/01, signed and sealed by Sonia A. Chance, P.E.

Manuel Perez, P.E. Product Control Examiner Product Control Division




WINDOW LENGTH

NON IMPACT RESISTANT WINDOWS


GLAZED WITH 3/16" ANNEALED OR TEMPERED GLASS MIAMI DADE COUNTY APPROVED IMPACT RESISTANT SHUTTERS REQUIRED SEE SHEETS 2, 3 AND 4.

LARGE MISSILE IMPACT RESISTANT WINDOWS GLAZED WITH 5/16", 7/16" OR 1/2" LAMINATED GLASS SHUTTERS NOT REQUIRED SEE SHEETS 2, 5 AND 6.



NOTES

- THIS STRUCTURE IS DESIGNED AS PER THE SOUTH FLORIDA BUILDING CODE 1994 EDITION FOR DADE COUNTY, ALSO FOR WIND LOADS AS PER ASCE 7-88 USING CORRESPONDING LOADS.
- 2. WOOD BUCKS BY OTHERS, MUST BE ANCHORED PROPERLY TO TRANSFER LOADS TO THE STRUCTURE.
- ANCHORS SHALL BE AS LISTED, SPACED AS SHOWN ON DETAILS. ANCHOR EMBEDMENT TO BASE MATERIAL SHALL BE BEYOND WALL DRESSING OR STUCCO.



ALLOWABLE LOADS FOR ALTERNATE SHAPES AS SHOWN ABOVE OR SIMILAR CAN BE VERIFIED BY INSCRIBING PICTURE WINDOW SHAPE WITHIN SQUARE OR RECTANGLE AS SHOWN IN DOTTED LINES AND OBTAINING ALLOWABLE LOADS FROM THOSE SHAPES.


Engr: DR. HUMAYOUN FAROOQ STRUCTURES FLA. PE # 16557

APPROVED AS COMPLYING WITH THE SOUTH FLORIDA BUILDING CODE DATE DEC 13 2941 BY MANUAL PRODUCT CONTROL DIVISION BUILDING CODE COMPLIANCE OFFICE ACCEPTANCE NO. 01 02 05


drawing no. W00-53

sheet 1 of 6

EXTERIOR



					CAPACIT								DESI	GN LOAD	CAPACITY	Y - PSF				NON IMPACT RESISTANT WINDOWS
			/16" ANNI			3	/16" TEME	PERED GLAS	SS			3	/16" ANNI	EALED GLAS	SS	3	3/16" TEMF	PERED GLA	SS	MIAMI DADE COUNTY APPROVED IMPACT RESISTANT SHUTTERS REQD.
WINDOW	DIMS.	ANCHORS	TYPE 'A'	ANCHORS	TYPE 'B'	ANCHORS	TYPE 'A'	ANCHORS	TYPE 'B'	WINDOV	V DIMS.	ANCHORS	TYPE 'A'	ANCHORS	TYPE 'B'	ANCHORS	S TYPE 'A'	ANCHORS	TYPE 'B'	IMPACI RESISTANT SHOTTERS REQU.
HTGIW	LENGTH	EXT. (+)	INT. (-)	EXT. (+)	INT. (-)	EXT. (+)	INT. (-)	EXT. (+)	INT. (-)	WIDTH	LENGTH	EXT. (+)	INT. (-)	EXT. (+)	INT. (-)	EXT. (+)	INT. (-)	EXT. (+)	INT. (-)]
18"		80.0	82.2	80.0	82.2	80.0	186.7	80.0	186.7	18"		59.5	59.5	59.5	59.5	80.0	154.5	80.0	154.5	CORPORATION SEE SHEET 4 FOR DETAILS
24"		61.7	61.7	61.7	61.7	80.0	140.0	: 80.0	140.0	24"		48.5	48.5	48.5	48.5	80.0	120.0	80.0	120.0	#10 SMS
30"	į	61.7	61.7	61.7	61.7	80.0	140.0	80.0	140.0	30"		-	-	-	_	80.0	96.0	80.0	99.6	3/16" TAPCONS OR
36"		61.7	61.7	61.7	61.7	80.0	120.0	80.0	140.0	36"	96"	_	_	-	-	80.0	80.0	80.0	86.2	3/16" TEKS 2 8
42"	24"	61.7	61.7	61.7	61.7	80.0	120.0	80.0	140.0	42"		_	_	_	_	76.8	68.6	76.8	76.8	SEE SHEET 4 FOR DETAILS
48"	4 [61.7	61.7	61.7	61.7	80.0	120.0	80.0	140.0	48"		_	_	_	-	70.0	60.0	70.0	70.0	
54"	Ī	59.5	59.5	59.5	59.5	80.0	120.0	80.0	135.0	18"		45.7	45.7	45.7	45.7	80.0	152.7	80.0	152.7	
60"		57.8	57.8	57.8	57.8	80.0	120.0	80.0	131.3	24"	-	45.7	45.7	45.7	45.7	80.0	118.1	80.0	118.1	C CC
66"	Ī	56.5	56.5	56.5	56.5	80.0	120.0	80.0	128.3	30"	108"	_	_	_	_	80.0	96.0	80.0	97.5	
72"	Ī	54.4	54.4	54.4	54.4	80.0	120.0	80.0	126.0	36"		_	_	_	_	80.0	80.0	80.0	84.0	OS 5 7 5
18"		80.0	82.2	80.0	82.2	80.0	160.0	80.0	186.7	42"		<u> </u>			_	70.4	68.6	70.4	70.4	* FAROOQ FERS, PLAN GRAN
24"		61.7	61.7	61.7	61.7	80.0	120.0	80.0	140.0	18"		40.3	40.3	40.3	40.3	80.0	152.0	80.0		SVER A
30"	Ī	49.3	49.3	49.3	49.3	80.0	96.0	80.0	112.0	24"		40.3	40.3	40.3	40.3	80.0			152.0	
36"	ľ	41.1	41.1	41,1	41.1	80.0	80.0	80.0	93.3	30"	114"			-		80.0	96.0	80.0	117.4	AL TOTAL TOT
42"		41.1	41.1	41.1	41.1	80.0	80.0	80.0	93.3	36"						80.0		80.0	96.7	
48"	36"	41.1	41.1	41.1	41.1	80.0_	80.0	80.0	93.3	18"		35.8	35.8			 	80.0	80.0	80.4	
54"	ľ	41.1	41.1	41.1	41.1	80.0	80.0	80.0	93.3					35.8	35.8	80.0	143.2	80.0	143.2	MINDOW
60"	ŀ	39.9	39.9	39.9	39.9	80.0	80.0	80.0	93.3	24"	120"		_			80.0	116.7	80.0	116.7	1
66"	ł	35.9	35.9	35.9	35.9	80.0	80.0	80.0	93.3	30"				<u>-</u>	-	80.0	96.0	80.0	96.0	_
72"	ŀ	30.5	30.5	30.5	30.5	80.0	80.0	80.0	93.3	36"			00.6		-	79.6	79.6	79.6	79.6	
18"		75.9	75.9	75.9	75.9	80.0	160.0			18"	4 20 11	28.6	28.6	28.6	28.6	80.0	114.4	80.0	114.4	
24"	1	61.7	61.7	61.7	61.7	80.0		80.0	172.3	24"	132"	-	_	<u> </u>	_	80.0	114.4	80.0	114.4	
30"	ŀ	49.3					120.0	80.0 ~	140.0	30"		-	_	_	-	80.0	94.8	80.0	94.8	S N
30 76"	ŀ		49.3	49.3	49.3	80.0	96.0	80.0	112.0	18"		23.2	23.2	23.2	23.2	80.0	92.8	80.0	92.8]
30	}	41.1	41.1	41.1	41.1	80.0	80.0	80.0	93.3	24"	144"	-			-	80.0	92.8	80.0	92.8	ا ف∥ ا
42"	48"	35.2	35.2	35.2	35.2	80.0	68.6	80.0	80.0	30"						80.0	92.8	80.0	92.8	
48"	ŀ	30.8	30.8	30.8	30.8	70.0	60.0	70.0	70.0	19-1/8"		77.4	77,4	77.4	77.4	80.0	175.7	80.0	175.7	
54"		30.8	30.8	30.8	30.8	70.0	60.0	70.0	70.0	26-1/2"		56.9	56.9	56.9	56.9	80.0	129.2	80.0	129.2	
60"				-	-	70.0	60.0	70.0	70.0	37"	26"	56.9	56.9	56.9	56.9	80.0	110.8	80.0	129.2	NOR S
66"	ŀ		-			70.0	60.0	70.0	70.0	53-1/8"		56.5	56.5	56.5	56.5	80.0	110.8	80.0	128.3	4
72"			_		<u>-</u>	70.0	60.0	70.0	70.0	19-1/8"		77.3	77.3	77.3	77.3	80.0	150.6	80.0	175.5	EXTER S71
18"	1	72.5	72.5	72.5	+	80.0	160.0	80.0	164.7	26-1/2"		55.8	55.8	55.8	55.8	80.0	108.7	80.0	126.8	
24"].	57.8	57.8	57.8	57.8	80.0	120.0	80.0	131.3	37"	38-3/8"	40.0	40.0	40.0	40.0	80.0	77.8	80.0	90.8	NOTE:
30"	ļ	43.5	43.5	43.5	43.5	80.0	96.0	80.0	112.0	53-1/8"		38.6	38.6	38.6	38.6	80.0	75.0	80.0	87.6	WIDTH AND LENGTH DIMENSIONS CAN BE 1 2
36"	ļ	39.9	39.9	39.9	39.9	80.0	80.0	80.0	93.3	19-1/8"		71.6	71.6	71.6	71.6	80.0	150.6	80.0	162.4	ORIENTED VERTICALLY OR HORIZONTALLY AS SHOWN ABOVE.
42"	60"	35.2	35.2	35.2	35.2	80.0	68.6	80.0	80.0	26-1/2"		55.8	55.8	55.8	55.8	80.0	108.7	80.0	126.8	AS SHOWN ABOVE.
48"		_	_		-	70.0	60.0	70.0	70.0	37"	50-5/8"	40.0	40.0	40.0	40.0	80.0	77.8	80.0	90.8	
54"	ļ	-	-			62.2	53.3	62.2	62.2	53-1/8"		29.2	29.2	29.2	29.2	66.4	56.9	66.4	66.4	
60"	l.					56.0	48.0	56.0	56.0	19-1/8"		69.7	69.7	69.7	69.7	80.0	150.6	80.0	158.3	
66"	ļ					56.0	48.0	56.0	56.0	26-1/2"		53.2	53.2	53.2	53.2	80.0	108.7	80.0	123.9	GESCLIDITION CHARMS REV. PER THE CHARMS REV. P
72"		-			_	56.0	48.0	56.0	56.0	37"	57"	40.0	40.0	40.0	40.0	80.0	77.8	80.0	90.8	
18"	ļ	70.5	70.5	70.5	70.5	80.0	160.0	80.0	160.0	53-1/8"		-			+0.0	63.2	54.2	63.2	63.2	SOUTH FLORIDA BUILDING CODE DATE DEC 1 3 2001
24"	Į.	54.4	54.4	54.4	54.4	80.0	120.0	80.0	126.0	19-1/8"		68.4	68.4	68.4	68.4	80.0	150.6	80.0	155.3	
30"	Į.	37.6	37.6	37.6	37.6	80.0	96.0	80.0	106.1	26-1/2"		48.4	48.4	48.4	48.4	80.0	108.7	80.0	120.4	BY Manuel sery 5 15 15 15 15 15 15 15 15 15 15 15 15 1
36"	72"	30.5	30.5	30.5	30.5	80.0	80.0	80.0	93.3	37"	63"	37.2	37.2	37.2	37.2	80.0	77.8	80.0	+	PRODUCT CONTROL DIVISION BUILDING CODE COMPLIANCE OFFICE
42"	-	<u>- : : </u>				80.0	68.6	80.0	80.0	53-1/8"		- 37.2	- 37.2	- 37.2	-	63.2	54.2	63.2	90.8	BUILDING CODE COMPLIANCE OFFICE
48"				· -		70.0	60.0	70.0	70.0	19-1/8"		66.6	66.6	66.6	66.6				63.2	ACCEPTANCE NO. O1-0102-05
54"		-	-	_		62.2	53.3	62.2	62.2	26-1/2"		44.8				80.0	150.6	80.0	151.2	
60"		_	~	_	_	56.0	48.0	56.0	56.0	37"	74-1/4"		44.8	44.8	44.8	80.0	108.7	80.0	115.8	Engr: DR. HUMAYOUN FAROOQ STRUCTURES FLA. PE # 16557
18"		69.1	69.1	69.1	69.1	80.0	156.8	80.0	156.8	53-1/8"			-		-	80.0	77.8	80.0	90.7	STRUCTURES FLA. PE # 16557
24"		51.2	51.2	51.2	51.2	80.0	120.0	80.0	122.5	130-1/0	L		<u> </u>	<u> </u>		63.2	54.2	63.2	63.2	
30"	Ī	33.1	33.1	33.1	33.1	80.0	96.0	80.0	102.3											scole:
36"	84"	-	_	-	-	80.0	80.0	80.0	89.1											
42"	ľ	-	_	-	_	80.0	68.6	80.0	80.0		٠.									drawing
48"			_	-	_	70.0	60.0	70.0	70.0											OCT 2 2001 WOO-
54"	Ī		_	_	 _	62.2	53.3	62.2	62.2						_					
										l .			· .							(sheet 3



	I	MPACT RE	SISTANT W	INDOWS (SI	HUTTERS NO	T REQUIRED	>			IMPACT RE	SISTANT W	INDOWS (SH	UTTERS NO	T REQUIRED)		. 0
				LOAD CAPA							DESIGN	LOAD CAPA	CITY - PS	SF			7
WINDOW	DIMS.	5/16" LAM.	ANN. GLASS	7/16" LAM.	H.S. GLASS	1/2" LAM.	H.S. GLASS	WINDOV	V DIMS.	5/16" LAM.	ANN. GLASS	7/16" LAM.	H.S. GLASS	1/2" LAM.	H.S. GLASS		
WIDTH I	LENGTH	EXT. (+)	INT. (-)	EXT. (+)	INT. (-)	EXT. (+)	INT, (-)	WIDTH	LENGTH	EXT. (+)	INT. (-)	EXT. (+)	INT. (-)	EXT. (+)	INT. (-)		IGN 978
18"	ŀ	70.0	70.0	65.0	65.0	73.3	75.0	18"		70.0	70.0	65.0	65.0	73.3	75.0	ANCHORS FOR THIS PAGE TO BE	OOQ CORPORATION PLANNERS & PRODUCT DESIGN 7 AVE IDA 33174 34-8100 FAX. (305) 262-6978
24"		70.0	70.0	65.0	65.0	73.3	75.0	24"		59.0	59.0	65.0	65.0	73.3	75.0	#14 SMS	71 11C
30"	ŀ	70.0 70.0	70.0 70.0	65.0	65.0 65.0	73.3	75.0	30"	96"	36.1	36.1	65.0	65.0	73.3	75.0	1/4" TAPCONS OR	A7
36" 42"	ŀ	70.0	70.0	65.0 65.0	65.0	73.3	75.0 75.0	36"		<u> </u>	-	65.0	65.0	73.3	75.0	1/4" TEKS SEE SHEET 6 FOR DETAILS	ON So
48"	24"	70.0	70.0	65.0	65.0	73.3	75.0	42" 48"			_	65.0 65.0	65.0 65.0	73.3 73.3	75.0	SEE SHEET O FOR DETAILS	Ϋ́P. XX.
54"		70.0	70.0	65.0	65.0	73.3	75.0	18"		55.3	55.3	65.0	65.0	73.3	75.0 75.0		20F RS 8 74
60"	ľ	70.0	70.0	65.0	65.0	73.3	75.0	24"		55.3	55.3	65.0	65.0	73.3	75.0	•	8 4 E C
66"	Ī	70.0	70.0	65.0	65.0	73.3	75.0	30"	108"	_	_	65.0	65.0	73.3	75.0		ANE 48
72"		66.7	66.7	65.0	65.0	73.3	75.0	36"		_	-	65.0	65.0	73.3	75.0		
18"		70.0	70.0	65.0	65.0	73.3	75.0	42"		-	_	65.0	65.0	73.3	75.0		AR RS, V 8, LOR
24"		70.0	70.0	65.0	65.0	73.3	75.0	18"		48.6	48.6	65.0	65.0	73.3	75.0		F. S.
30"		70.0	70.0	65.0	65.0	73.3	75.0	24"	114"	48.6	48.6	65.0	65.0	73.3	75.0		L ((()
36"	ŀ	65.5	65.5	65.0	65.0	73.3	75.0	30"	,,,	<u> </u>	-	65.0	65.0	73.3	75.0		M 2 E N E
42"	36"	57.4	57.4	65.0	65.0	73.3	75.0	36"		-	-	65.0	65.0	73.3	75.0		
48"		51.0	51.0	65.0	65.0	73.3	75.0	18"		43.0	43.0	65.0	65.0	73.3	75.0		MO
54"		45.1 40.8	45.1 40.8	65.0	65.0 65.0	73.3 73.3	75.0	24"	120"	43.0	43.0	65.0	65.0	73.3	75.0		WINDOW
60" 66"	}	37.1	37.1	65.0 65.0	65.0	73.3	75.0 75.0	30" 36"				65.0	65.0	73.3	75.0		×
72"	ŀ	33.1	33.1	65.0	65.0	73.3	75.0	18"		34.6	34.6	65.0 65.0	65.0 65.0	73.3 73.3	75.0	<u> </u>	
18"		70.0	70.0	65.0	65.0	73.3	75.0	24"	132"	37.0	34.0	65.0	65.0	73.3	75.0 75.0	·	FIXED INC.
24"	Ì	70.0	70.0	65.0	65.0	73.3	75.Q	30"	132		_	65.0	65.0	73.3	75.0 75.0		
30"]	61.0	61.0	65.0	65.0	73.3	75.0	18"		28.6	28.6	65.0	65.0	73.3	75.0		ALUM CO. 1 ST. 10-2
36"		51.0	51.0	65.0	65.0	73.3	75.0	24"	144"	_	_	65.0	65.0	73.3	75.0		
42"	48"	54.1	54.1	65.0	65.0	73.3	75.0	30"		_	-	65.0	65.0	73.3	75.0		AZEC MFC 8TH 33(
48"	-~`	49.0	49.0	65.0	65.0	73.3	75.0	19-1/8"		70.0	70.0	65.0	65.0	73.3	75.0		GLAZED ON MFG. 18TH FL. 330
54"		44.4	44.4	65.0	65.0	73.3	75.0	26-1/2"		70.0	70.0	65.0	65.0	73.3	75.0	\ \	
60"		40.4	40.4	65.0	65.0	73.3	75.0	37"	26"	70.0	70.0	65.0	65.0	73.3	75.0		OGR WESTAH,
66"	}	-	-	65.0	65.0	73.3	75.0	53-1/8"		67.2	67.2	65.0	65.0	73.3	75.0	NOTE:	
72"		70.0	70.0	65.0	65.0	73.3 73.3	75.0	19-1/8"		70.0	70.0	65.0	65.0	73.3	75.0	WIDTH AND LENGTH DIMENSIONS CAN BE ORIENTED VERTICALLY OR HORIZONTALLY AS SHOWN ABOVE.	XAL 671 HAL
18" 24"	ŀ	70.0	70.0 70.0	65.0 65.0	65.0 65.0	73.3	75.0 75.0	26-1/2"	38-3/8"	70.0	70.0	65.0	65.0	73.3	75.0		
30"	1	49.3	49.3	65.0	65.0	73.3	75.0	37"	00 0/0	61.3	61.3	65.0	65.0	73.3	75.0		
36"	1	40.8	40.8	65.0	65.0	73.3	75.0	53-1/8"		53.0	53.0	65.0	65.0	73.3	75.0	·	
42"		44.2	44.2	65.0	65.0	73.3	75.0	19-1/8"		70.0	70.0	65.0	65.0	73.3	75.0		ASTM
48"	60"	40.4	40.4	65.0	65.0	73.3	75.0	26-1/2"	50-5/8"	68.2	68.2	65.0	65.0	73.3	75.0	a control of the cont	
54"	Ī	_	_	65.0	65.0	67.1	67.1	37" 53-1/8"		47.7 43.5	47.7 43.5	65.0 65.0	65.0	73.3	75.0		
60"			_	60.4	60.4	60.4	60.4	19-1/8"		70.0	70.0	65.0	65.0 65.0	71.6 73.3	71.6 75.0		
66"	j	-		60.4	60.4	60.4	60.4	26-1/2"		61.4	61.4	65.0	65.0	73.3	75.0		description CHARTS REV. PER .
72"				60.4	60.4	60.4	60.4	37"	57"	41.8	41.8	65.0	65.0	73.3	75.0		 6
18"]	70.0	70.0	65.0	65.0	73.3	75.0	53-1/8"		_	-	65.0	65.0	68.2	68.2	·	λą
24"		66.7	66.7	65.0	65.0	73.3	75.0	19-1/8"		70.0	70.0	65.0	65.0	73.3	75.0		i oi
30"	- 1	43.3	43.3	65.0	65.0	73.3	75.0	26-1/2*	63"	59.5	59.5	65.0	65.0	73.3	75.0		revisions: no date A 10.02.01
36" 42"	72"	33.1	33.1	65.0 65.0	65.0 65.0	73.3 73.3	75.0 75.0	37"	63	38.0	38.0	65.0	65.0	73.3	75.0		
48"				65.0	65.0	73.3	75.0	53-1/8"	ļ	-		65.0	65.0	68.2	68.2		
54"				65.0	65.0	67.1	67.1	19-1/8"		70.0	70.0	65.0	65.0	73.3	75.0		8 -
60"		-		60.4	60.4	60.4	60.4	26-1/2"	74-1/4"	54.1	54.1	65.0	65.0	73.3	75.0	Engr: DR. HUMAYOUN FAROOQ STRUCTURES	2
18"		70.0	70.0	65.0	65.0	73.3	75.0	37"		31.0	31.0	65.0	65.0	73.3	75.0	FLA. PE # 16557 APPROVED AS COMPLYING WITH THE	12-12- 1/2" == HAMID
24"		62.4	62.4	65.0	65.0	73.3	75.0	53-1/8"	L		-	65.0	65.0	68.2	68.2	SOUTH FLORIDA BUILDING CODE	;;
30"		40.3	40.3	65.0	65.0	73.3	75.0				•					DATE DEC 1 3 2901	date:
36*	84"	-		65.0	65.0	73.3	75.0								Ç	BY Manuel Seres	
42"			_	65.0	65.0	73.3	75.0									PRODUCT CONTROL DIVISION	drawing n
48"			-	65.0	65.0	73.3	75.0					•				OCT 2 2001 BUILDING CODE COMPLIANCE OFFICE	W00-5
54"			-	65.0	65.0	67.1	67.1	<u> </u>					-			OCT 2 2001 ACCEPTANCE NO. O1-O1 OZ. O5	sheet 5 of

 \sim

